L-SERIES LINCOLN PNEUMATIC FEMALE THREADED PLUG





FECHA
: 11/23/2026 09:49 PM

SKU
: 16228

MARCA
: DIXON VALVE

MODELO
: L2F2

Construction:
Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:
Lincoln Long-Nose Automotive Interchange
Parker 70-Series, Tomco Series-1110, Coilhose Type-17

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Burst Pressure	5000 PSI (345 bar)
Factory Part Number	L2F2
Hex	5/8"
Length	2.10"
Material	Steel
Maximum OD	0.72"
Maximum Operating Pressure	300 PSI (21 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread	NPT
Thread Size	1/4"
Weight Lb	0.0500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us