# WILKERSON FRL'S L40 & L50 ECONOMIST® STANDARD LUBRICATOR




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 02:11 AM

SKU
: 26420

MARCA
: DIXON VALVE

MODELO
: L40-0BAMB

Use:
The rate of oil delivery may be controlled by turning the adjusting screw counter clockwise for more and clockwise for less oil delivery. The oil delivery rate will change automatically to deliver more oil during higher air flows and less oil for air flows lower than the one at which the setting was made.
Can be filled under pressure
For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:
26 oz. bowl
Metal Bowl
Manual drain with sight glass
Full view sight dome
Adjustable oil feed
Quick-disconnect clamp ring for easy bowl removal

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 120 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Description** | Metal Bowl, manual drain with sight glass |
| **Factory Part Number** | L40-0BAMB |
| **Flow** | 927 SCFM |
| **Maximum Operating Pressure** | 200 PSIG (13.8 Bar) |
| **Port** | 1-1/2" |
| **Temperature Range** | 32°F to 150°F (0°C to 65.5°C) |
| **Weight Lb** | 9.7900 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us