WILKERSON FRL'S L40 & L50 ECONOMIST® STANDARD LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:51 AM

SKU
: 26421

MARCA
: DIXON VALVE

MODELO
: L50-0CA

Use:
The rate of oil delivery may be controlled by turning the adjusting screw counter clockwise for more and clockwise for less oil delivery. The oil delivery rate will change automatically to deliver more oil during higher air flows and less oil for air flows lower than the one at which the setting was made.
Can be filled under pressure
For all Wilkerson lubricators, use any petroleum-base, non-detergent light weight oil (SAE 10/150 SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil. Do not use any synthetic oil or oils containing additives or solvents.

Features:
26 oz. bowl
Transparent Bowl
Solid bottom
Full view sight dome
Adjustable oil feed
Quick-disconnect clamp ring for easy bowl removal

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 120 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Transparent Bowl, solid bottom
Factory Part Number	L50-0CA
Flow	1186 SCFM
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	2"
Temperature Range	32°F to 125°F
Weight Lb	10.0750

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us