L73 SERIES 1 FRL'S COMPACT MICRO-FOG LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:49 PM

SKU
: 26440

MARCA
: DIXON VALVE

MODELO
: L73M-4MB

Applications:
Micro-fog lubricators, identified by a red adjusting screw, are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Use:
Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:
Metal Bowl
4 oz. reservoir
Quick release bayonet bowl
Micro-fog design delivers aerosol mist

How it works:
Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Installation
In-line or modular installation

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
Micro-fog lubricators cannot be filled under pressure.
Pressure rating given at ambient temperature 70°F/21°C.
SCFM ratings at 90 PSIG inlet pressure

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Description	Metal Bowl
Factory Part Number	L73M-4MB
Flow	70 SCFM
Maximum Operating Pressure	250 PSI
Maximum Temperature	175°F (79°C)
Port	1/2"
Weight Lb	1.2500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us