L74 SERIES 1 FRL'S STANDARD OIL-FOG LUBRICATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:35 AM

SKU
: 26446

MARCA
: DIXON VALVE

MODELO
: L74C-6

Applications:
Oil-fog lubricators, identified by a green adjusting screw, are used for lubricating a single air tool or air motor, and are located as near the device as possible.

Use:
Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F

Features:
Transparent Bowl
7 oz. reservoir
Quick release bayonet bowl
Can be filled under pressure

How it works:
All the oil visible dropping through the transparent sight-feed dome goes to the airstream.

Installation
In-line or modular installation

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
Pressure rating given at ambient temperature 70°F.
SCFM ratings at 90 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Transparent Bowl
Factory Part Number	L74C-6
Flow	186 SCFM
Maximum Operating Pressure	150 PSI
Maximum Temperature	125°F (52°C)
Port	3/4"
Weight Lb	1.7100

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us