SERIES 1 STANDARD MICRO-FOG LUBRICATOR WITH HIGH PRESSURE SIGHT FEED DOME



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:29 AM

SKU
: 24889

MARCA
: DIXON VALVE

MODELO
: L74M-4MBPX

Applications:
Micro-fog lubricators are used for applications containing one or more points of lubrication, cylinders and multiple or single tools.

Use:
Designed for use with alcohol or other anti-freeze agents when units are installed in cold temperature environments.
Recommended lubricants: misting type oil rated 50 to 200 SSU (ISO Grade 7 to 46) at 100°F (38°C)

Features:
Metal Bowl with Sight Glass
7 oz. reservoir
Quick release bayonet bowl
Micro-fog design delivers aerosol mist
High pressure dome with aluminum case and fluorocarbon O-Rings and seals;
High pressure sight glass on bowls and metal petcock drain.

How it works:
Air flow through the lubricator lifts oil from the reservoir to the sight-feed dome. Oil is dropped into the fog generator and atomized into a fine mist. Lightweight particles are delivered downstream for lubrication. Heavier particles fall back into the reservoir.
The micro-fog lubricator delivers 10% of the oil drops visible through the transparent sight-feed dome.

Installation
In-line or modular installation

Safety notes:
FRL's are designed for air service only, unless otherwise indicated.

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Micro-fog lubricators cannot be filled under pressure.

Pressure rating given at ambient temperature 70°F.

SCFM ratings at 90 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	L74M-4MBPX
Flow	154 SCFM
Maximum Temperature	175°F (79°C)
Port	1/2"
Weight Lb	2.7810

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us