WILKERSON LOCKOUT VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:29 PM

SKU
: 16345

MARCA
: DIXON VALVE

MODELO
: LV6N6D

Applications:
Lockout valves are installed in pneumatic drop legs, or individual pneumatic control lines. In accordance with OSHA procedures, lockout valves are used during maintenance and service procedures of pneumatically (air) operated equipment.

Use:
Inline or surface mountable

Specifications:
Used to comply with OSHA 29 CFR part 1910
Built in port for pressure verification to meet ANSI B11 and Pmm 155 requirements

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	LV6N6D
Material	Yellow Cast Aluminum with Red Handle
Port	3/4" In/Out, 3/4" Exhaust
Pressure Range	15-300 PSI
Temperature Range	40°F to 175°F (4.4°C to 18.6°C)
Weight Lb	2.0000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us