M-SERIES ARO PNEUMATIC FEMALE THREADED PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:57 PM

SKU
: 24936

MARCA
: DIXON VALVE

MODELO
: M2F2-B

Specifications:
Rated pressure for connected Auto Brass Coupler & Brass Plug: 300 PSI (20 bar) Maximum Working and 5,000 PSI (345 bar) Burst
Rated pressure for connected Manual Brass Coupler & Brass Plug: 300 PSI (20 bar) Maximum Working and 12,700 PSI (876 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:
Automatic couplings interchange with ARO 210/310 and Hansen 210/310
Manual Couplings Interchange with Parker 50-Series and Amflow Type 'B'

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	M2F2-B
Hex	11/16"
Length	1.57"
Material	Brass
Maximum OD	0.79"
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	1/4"
Weight Lb	0.0700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us