M-SERIES ARO PNEUMATIC MALE THREADED PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:36 PM

SKU
: 24939

MARCA
: DIXON VALVE

MODELO
: M2M2

Specifications:
Rated pressure for connected Auto Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 2,600 PSI (179 bar) Burst
Rated pressure for connected Manual Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 12,400 PSI (855 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Automatic couplings interchange with ARO 210/310 and Hansen 210/310
Manual Couplings Interchange with Parker 50-Series and Amflo Type 'B'

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Factory Part Number	M2M2
Hex	9/16"
Length	1.60"
Material	Steel
Maximum OD	0.65"
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	1/4"
Weight Lb	0.0500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us