MINI NEEDLE VALVE MALE TO FEMALE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:43 PM

SKU
: 16578

MARCA
: DIXON VALVE

MODELO
: MFC404

Specifications:
Flow coefficient: 0.44
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
A FKM O-ring seal and a PTFE back-up ring below the threads protects the mini valve from corrosion and galling.
Stem threads are rolled for strength and ease of operation

Construction:
316 Stainless Steel Stem

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Orifice	0.187"
Style	T Design Handle
Thread	NPT
Thread Size	1/2"-14
Factory Part Number	MFC404
Material	Zinc-Nickel Plated Steel
Pressure Rating	10000 PSI at 200°F (10000 PSI at 94°C)
Seal	FKM O-ring

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Seat	Metal-to-Metal Hard Seat
Weight Lb	1.3400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us