# BLOCK AND BLEED NEEDLE VALVE




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:11 PM

SKU
: 16581

MARCA
: DIXON VALVE

MODELO
: MFC702

Specifications:
Flow coefficient: 0.44

Features:
Allows pressure to be bled off without disturbing the permanent piping installation allowing quick and easy removal or replacement of instruments
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation
0.090" bleed hole located on bottom is controlled by a 1/4"- 20 UNF-2A bleed screw

Construction:
Male to Female
316 Stainless Steel Stem
Handle Style: T Design

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Orifice** | 0.187" |
| **Thread** | NPT |
| **Thread Size** | 1/4" - 18 |
| **Factory Part Number** | MFC702 |
| **Material** | Zinc Nickel Plated Steel |
| **Pressure Rating** | 6000 PSI at 200°F (6000 PSI at 94°C) |



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Seal** | FKM O-ring |
| **Seat** | Soft Seat |
| **Weight Lb** | 1.3400 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us