BLOCK AND BLEED NEEDLE VALVE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:00 PM

SKU
: 16582

MARCA
: DIXON VALVE

MODELO
: MFC704

Specifications:
Flow coefficient: 0.44

Features:
Allows pressure to be bled off without disturbing the permanent piping installation allowing quick and easy removal or replacement of instruments
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation
0.090" bleed hole located on bottom is controlled by a 1/4"- 20 UNF-2A bleed screw

Construction:
Male to Female
316 Stainless Steel Stem
Handle Style: T Design

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Orifice	0.187"
Thread	NPT
Thread Size	1/2" - 18
Factory Part Number	MFC704
Material	Zinc Nickel Plated Steel
Pressure Rating	6000 PSI at 200°F (6000 PSI at 94°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Seal	FKM O-ring
Seat	Soft Seat
Weight Lb	1.3700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us