BLEED NEEDLE VALVE

FECHA
: 11/23/2026 09:37 PM

SKU
: 16756

MARCA
: DIXON VALVE

MODELO
: MS852



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Specifications:
Metal-to-metal hard seat design is 100% helium leak tested to 1 x 10-4 ml/s at 200 PSI

Features:
Provides a convenient means to relieve process pressures trapped between a shut-off valve and the instrument.
FKM O-ring and PTFE back- up ring below the threads protects from corrosion and galling
Stem threads are rolled for strength and ease of operation
Features a non-rotating soft tip stem and a back-up metal-to-metal seal

Construction:
316 Stainless Steel Stem
Handle Style: T Design
0.159" bleed port

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Male Thread	NPT
Male Thread Size	1/4" - 18
Style	Soft Tip
Factory Part Number	MS852
Material	316 Stainless Steel
Pressure Rating	6000 PSI at 200°F (6000 PSI at 94°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Seal	FKM O-ring
Weight Lb	1.3400

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us