DIX-LOCK® N-SERIES INTERCHANGE MALE HEAD X MALE THREADED SAFETY-LOCK END PLUG

FECHA
: 11/24/2026 12:54 AM

SKU
: 25102

MARCA
: DIXON VALVE

MODELO
: N4M6-ZLS





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Specifications:
Rated pressure for connected Steel Coupler & Steel Plug: 500 PSI (35 bar) Maximum Working and 11,000 PSI (755 bar) Burst
Conforms to MIL-C-3486 and A-A-50431A standards

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Coupling sleeve constructed of cast zinc steel
Steel lock ring

Available Options:
316 stainless steel available in some versions upon request, contact Dixon

Compatibility & Interchange Data:
Bowes Interchange Bayonet Style
Interchangeable with Bowes 51000-Series, National Series 'B', MacDonald Quick-Action, Campbell Single-Lock

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/2"
Hex	1-3/16"
Length	3.65" (92.7mm)
Material	Steel
Maximum OD	1.31" (33.3mm)
Factory Part Number	N4M6-ZLS
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPTF
Thread Size	3/4"
Weight Lb	0.7000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us