SPIRAL HOSE AND CABLE PROTECTION STANDARD



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:36 PM

SKU
: 17036

MARCA
: DIXON VALVE

MODELO
: NFSGX63

Applications:
Used in mining, quarrying, forestry, offshore industries and most hydraulic hose applications

Use:
Can be used on single or multiple hose bundles

Features:
Not flame retardant
Crush and high abrasion resistance
Chemical and UV ray resistant
Self-lubricating to reduce hose wear
Easy to install on-site
Smooth radius on all edges

Note:
Sold in coil lengths only
Spiral guard ID is equal to the guard at rest

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	NFSGX63
Nominal ID	2.0"
Range	2.05" to 2.95"
Temperature Range	-40°F to 248°F (-40°C to 120°C)
Weight Lb	26.1000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us