DIXON FRAC FITTING O-RING



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:54 PM

SKU
: 25140

MARCA
: DIXON VALVE

MODELO
: O347BU

Applications:
Used in the fast paced transfer of water and sand slurry to a hydraulic fracturing site.

Use:
For use with Dixon Frac Fittings

Safety notes:
400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with Dixon carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD
When assembling hose with abrasion resistant covers, such as UHMW polyethylene, you will need to use Dixon's heavy duty (HD) carbon steel ferrule part numbers CF400-6CSHD through CF400-16CSHD. Other size HD ferrules are available upon request.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	O347BU
Material	Buna-N
Optional Pkg/Box Qty	1
Size	4"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us