# STAINLESS PANEL BUILDER GAUGE




** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:30 PM

SKU
: 17182

MARCA
: DIXON VALVE

MODELO
: PBLSS400

Applications:
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Use:
Suitable for corrosive environments
Used in gaseous and liquid media

Specifications:
ASME B40.100 Grade A ± 2-1-2% full scale accuracy

Features:
Fits industry standard 2.56" panel hole cutout

Construction:
316L stainless steel wetted parts materials
304 stainless steel case and ring
Dial- white aluminum with black lettering; stop pin
Pointer- black aluminum
Glycerin filled
Laminated safety glass window lens

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Factory Part Number** | PBLSS400 |
| **Figure Interval** | 100 |
| **Material** | Stainless Steel |
| **Minor Gradient** | 10 |
| **Mount** | 1/4" Lower Back Mount |
| **Pressure Range** | 0-400 PSI |
| **Size** | 2-1/2" Face |
| **Temperature Range** | -4°F to 140°F (-20°C to 60°C) |
| **Temperature Rating** | 212°F (100°C) maximum media temperature |
| **Weight Lb** | 0.4900 |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us