PD-SERIES DIAGNOSTIC MALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:36 PM

SKU
: 17203

MARCA
: DIXON VALVE

MODELO
: PD1M2

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Compatibility & Interchange Data:
Interchangeable to ISO15171-1
Parker PD-Series, Aeroquip FD90

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1/8"
Burst Pressure	18700 PSI (1300 bar)
Factory Part Number	PD1M2
Hex	17mm
Length	1.48" (37.6mm)
Material	Steel
Maximum OD	0.76" (19.3mm)
Maximum Operating Pressure	6000 PSI (400 bar) at 70°F (21°C)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Thread	Male NPT

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Thread Size	1/4"-18
Weight Lb	0.0700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us