PROCESS GAUGE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 05:24 PM

SKU
: 17235

MARCA
: DIXON VALVE

MODELO
: PGS30

Applications:
Specifically designed for process, chemical and petroleum industries, these process gauges are engineered to deliver years of accurate service while withstanding vibration, corrosive media and corrosive atmosphere.

Specifications:
Accuracy: ± 0.5% ANSI/ASME Grade 2A

Construction:
Case: black impact resistant thermoplastic, with safety blowout back, solid front, integral back flange (dry)
Ring: ethylene propylene
Wetted parts: 316L stainless steel
Window: polycarbonate
Dial: white aluminum
Scale: single scale PSI only
Pointer: black aluminum

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	PGS30
Figure Interval	5
Minor Gradient	.2
Mount	1/2" Lower Mount
Pressure Range	0-30 PSI
Size	4-1/2" Face
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Weight Lb	2.0020

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us