DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER- RETAIL PACKAGE





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:43 PM

SKU
: 17684

MARCA
: DIXON VALVE

MODELO
: PW-2EM2-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1/4"
Burst Pressure	20,800 PSI (1,434 Bar)
Description	1/4" straight thru couplers (Case Qty 20 Required)
Male Thread	NPTF
Male Thread Size	1/4"-18
Mandatory Pkg/Box Qty	20
Material	Brass
Maximum Operating Pressure	5,200 PSI (359 Bar)
Factory Part Number	PW-2EM2-B
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.1500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us