DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE PLUG- RETAIL PACKAGE

FECHA
: 11/23/2026 08:27 PM

SKU
: 17699

MARCA
: DIXON VALVE

MODELO
: PW-E3F3-B



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	3/8"
Burst Pressure	10,800 PSI (745 Bar)
Description	3/8" straight thru nipples (Case Qty 20 Required)
Female Thread	NPTF
Female Thread Size	3/8"-18
Hex	7/8"
Length	1.60 (40.6mm)
Mandatory Pkg/Box Qty	20

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Material	Brass
Maximum OD	1.01 (25.7mm)
Maximum Operating Pressure	2,700 PSI (186 Bar)
Factory Part Number	PW-E3F3-B
Weight Lb	0.1500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us