DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE PLUG- RETAIL PACKAGE

FECHA
: 11/23/2026 09:30 PM

SKU
: 17700

MARCA
: DIXON VALVE

MODELO
: PW-E3M3



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series
These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel nipples are hardened to provide heavy duty performance.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	3/8"
Burst Pressure	14,000 PSI (966 Bar)
Description	3/8" straight thru nipples (Case Qty 20 Required)
Hex	3/4"
Length	1.69 (42.9mm)
Male Thread	NPTF
Male Thread Size	3/8"-18

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Mandatory Pkg/Box Qty	20
Material	Steel
Maximum OD	0.79 (20.1mm)
Maximum Operating Pressure	3,500 PSI (241 Bar)
Factory Part Number	PW-E3M3
Weight Lb	0.1000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us