WILKERSON FRL'S R16 COMPACT REGULATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:20 PM

SKU
: 26526

MARCA
: DIXON VALVE

MODELO
: R16-02R

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-125 PSI adjusting range
Self-relieving standard
Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

Available Options:
Available with 0-60 PSI adjusting range, contact Dixon for pricing and availability.

Installation
Can be installed with the adjusting knob in any position

Note:
Use a GC230 gauge (not supplied)

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	R16-02R
Flow	71.5 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	1/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.6900

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us