WILKERSON FRL'S R21 DIAL AIR REGULATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:45 PM

SKU
: 26557

MARCA
: DIXON VALVE

MODELO
: R21-03RG

Use:
Dial regulators feature a transparent, pressure-calibrated, non-rising adjustment dial for quick adjustment of secondary pressure.
The full reduced pressure range can be dialed in less than 270° of dial rotation. This feature is particularly advantageous if secondary pressure must be changed frequently.
All dial-air units have a slight constant air bleed.

Features:
0-160 PSI adjusting range
Balanced valve design
Relieving type
Non-rising pressure adjusting dial
Piston operated
One 1/4" NPT gauge port standard, can be used for additional outlet ports
Includes a GC230 gauge

Installation
Dial air regulators can be mounted in any position so dial face is always visible.

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	R21-03RG
Flow	180 SCFM
Includes	With Gauge
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	3/8"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	2.5800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us