WILKERSON FRL'S R28 STANDARD REGULATOR



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:33 PM

SKU
: 26572

MARCA
: DIXON VALVE

MODELO
: R28-03RG

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-125 PSI adjusting range
Self-relieving standard
Four adjusting pressure ranges available
Two 1/4" NPT gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges.
Supplied with a gauge

Safety notes:
FRL\'s are designed for air service only, unless otherwise indicated.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	R28-03RG
Flow	228 SCFM
Includes	With Gauge
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	3/8"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.7800

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us