GROOVED RIGID COUPLING-SERIES R, STYLE 5



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:07 PM

SKU
: 17819

MARCA
: DIXON VALVE

MODELO
: R76

Applications:
Ideal for fire protection, plumbing, low pressure air and drainage.

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 2
Bolt Size: 5/8"
Bolt Length: 3-1/4"

Features:
Lightweight and low pressure
Small gripping teeth hold the housing into the groove allowing a straight run of pipe and preventing any flex at the joint.

Construction:
Galvanized ductile iron body

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	R76
Material	Ductile Iron
Max. End Load Lbs.	27570
Maximum Operating Pressure	175 PSI at 70°F (21°C)
Nominal Size	6"
Pipe OD	6.625"
Seal	EPDM
Weight Lb	6.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us