KING COMBINATION NIPPLE NPT THREADED



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:30 PM

SKU
: 18304

MARCA
: DIXON VALVE

MODELO
: RST40

Applications:
Recommended for low-pressure discharge and suction service for compatible liquids

Use:
Crimp sleeves are available and recommended for reliable assemblies.

Construction:
NPT threaded end no knurl

Safety notes:
King Combination Nipples are not recommended for steam.
The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon for recommendations.
In accordance with the R.M.A. bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1-1/2 times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Rubber Manufacturers Association (R.M.A.) handbook.
Not for compressible products such as air or nitrogen
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	RST40
Material	316 Stainless Steel
Size	4"
Weight Lb	4.4700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us