# SINGLE CLAPPER SIAMESE CONNECTION BACK OUTLET



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 06:04 PM

SKU
: 19013

MARCA
: DIXON VALVE

MODELO
: SCS4025F

Applications:
Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:
UL listed
ULC listed
Factory Mutual approved

Features:
The swing clapper design provides an unobstructed waterway.
Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:
Single swing clapper with (2) pin lug swivel inlets.

Available Options:
Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## ESPECIFICACIONES TÉCNICAS

| | |
|---|---|
| **Branding** | Auto-Sprinkler |
| **Factory Part Number** | SCS4025F |
| **Inlet** | (2) 2-1/2" female NST (NH) |
| **Mandatory Pkg/Box Qty** | 1 |
| **Material** | Cast Brass |
| **Maximum Operating Pressure** | 250 PSI |
| **Origin** | U.S. |
| **Outlet** | 4" female NPT |
| **Weight Lb** | 10.9200 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us