GROOVE X GROOVE CHECK VALVE

FECHA
: 11/23/2026 10:57 PM

SKU
: 27640

MARCA
: DIXON VALVE

MODELO
: SCVV400



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
Single check valves are used in Fire Protection Systems to allow water flow in one direction only.
Typical applications include: at connections between public water supplies and private fire services systems, at discharges from fire pumps, at gravity tank connections, at fire department pumper connections
Use:
For horizontal and vertical installation
Specifications:
UL listed
Construction:
Brass
Supplied with a 1/4" and 1/2" tapped NPT port below the clapper and a 1/4" tapped NPT port above the clapper
Supplied with a 1-1/2" NPT tapped boss below the clapper. Boss above the clapper may be tapped for addition of a 1/2" NPT drain.
Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Inlet	4" Groove
Material	Brass
Maximum Operating Pressure	250 PSI
Outlet	4" Groove
Factory Part Number	SCVV400
Weight Lb	20.8000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us