SURELOCK? MALE NPT END



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:51 PM

SKU
: 19439

MARCA
: DIXON VALVE

MODELO
: SL038M

Applications:
Coupling for air service only, commonly used in construction and mining; excels in services where ease, economy, safety and speed are paramount

Features:
The pressure activated gasket allows easy coupling (less than 15 lbs. of force is required to connect the coupling) and gaskets seal upon introduction of line pressure.

Construction:
Body: SG iron AS1831 400-250-12
Bellow seal: natural rubber (patent pending)
Safety pin is supplied with each coupling

Available Options:
Other seal materials are available upon request, contact Dixon.

Safety notes:
Safety pin is supplied with each coupling and is required as a safety precaution
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	SL038M
Material	Iron
Seal	Natural Rubber
Size	3/8"
Style	Small Head
Weight Lb	0.6000
Working Pressure	200 PSIG at 70°F (21°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us