STAINLESS STEEL BALL VALVE REDUCED PORT, LOCKING HANDLE



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:10 AM

SKU
: 19733

MARCA
: DIXON VALVE

MODELO
: SSLBV50SP

Applications:
For use in water, oil and gas applications

Features:
Blow-out proof stem
Reduced port
Lockable

Construction:
316 stainless steel body, ball and stem
R-PTFE seat, joint gasket and thrust washer
Plastic cover on handle

Safety notes:
Not recommended as a throttling valve
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Saturated Steam Pressure	100 PSI
Temperature Range	-20°F to 356°F (-29°C to 180°C)
Thread	female NPT x female NPT
Factory Part Number	SSLBV50SP
Material	316 Stainless Steel
Pressure Rating	1000 PSI WOG
Seat	R-PTFE
Size	1/2"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Weight Lb	0.3500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us