DQC V-SERIES SNAP-TITE H/IH INTERCHANGE VALVED MALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:02 AM

SKU
: 21475

MARCA
: DIXON VALVE

MODELO
: V10JM10

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Steel nipples are machined from high-strength steel and induction hardened.

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075
Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel
Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/4"
Burst Pressure	5000 PSI (345 bar)
Factory Part Number	V10JM10
Hex	2"
Length	3.46"
Material	Steel
Maximum OD	2.19"
Maximum Operating Pressure	1750 PSI (120 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Male JIC
Thread Size	1-5/8"-12
Weight Lb	1.4600

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us