DQC V-SERIES SNAP-TITE H/IH INTERCHANGE UNVALVED MALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:19 AM

SKU
: 21494

MARCA
: DIXON VALVE

MODELO
: V12M12-E

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Steel nipples are machined from high-strength steel and induction hardened.

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/2"
Burst Pressure	10000 PSI (700 bar)
Factory Part Number	V12M12-E
Hex	2-1/8"
Length	2.34"
Material	Steel
Maximum OD	2.33"
Maximum Operating Pressure	5000 PSI (345 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Male NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us

Weight Lb	1.0800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us