
DQC V-SERIES SNAP-TITE H/IH INTERCHANGE UNVALVED FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 11:03 PM

SKU
: 21602

MARCA
: DIXON VALVE

MODELO
: V6F6-B-E

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Machined components are manufactured using solid bar stock

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Body Size	3/4"
Burst Pressure	11100 PSI (750 bar)
Factory Part Number	V6F6-B-E
Hex	1-3/16"
Length	1.86" (47.2mm)
Material	Brass
Maximum OD	1.31" (33.3mm)
Maximum Operating Pressure	3500 PSI (250 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us

Weight Lb	0.2300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us