DQC V-SERIES SNAP-TITE H/IH INTERCHANGE VALVED MALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 12:52 AM

SKU
: 21611

MARCA
: DIXON VALVE

MODELO
: V6M6-SS

Features:
General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:
Machined components are manufactured using solid bar stock

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075
Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel
Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged
Oxy-clean treatment is available

Compatibility & Interchange Data:
Interchangeable to MIL-C-51234
Snap-Tite H and Faster TNV

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	3/4"
Burst Pressure	7500 PSI (500 bar)
Factory Part Number	V6M6-SS
Hex	1-1/2"
Length	2.91" (73.9mm)
Material	316 Stainless Steel
Maximum OD	1.65" (41.9mm)
Maximum Operating Pressure	2000 PSI (130 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Male NPTF
Thread Size	3/4"-14
Weight Lb	0.6300

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us