KING CABLE® HOSE-TO-HOSE SERVICE

FECHA
: 11/23/2026 09:33 PM

SKU
: 25634

MARCA
: DIXON VALVE

MODELO
: WB3



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

Applications:
When hose, couplings or clamps fail, or there is an accidental separation of the assembly, King safety cables minimize damage to equipment and injuries to operators.

Features:
King cable is the low cost answer to eliminate injuries caused by broken air hose connections
King safety cable reaches across the hose fittings to provide standby safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose.
Thoroughly tested with years of service. A positive safeguard for air hose connections- helps you meet today's safety standards.
Highly resistant to rust and corrosion

Construction:
Wire Rope: Galvanized Carbon Steel
Ferrules: Aluminum
Springs: Galvanized Carbon Steel

Installation
Must be installed in the extended position (no slack)
No tools needed- easy to install and remove

Note:
Cables are shipped with safety restraint labels attached

Safety notes:
King Safety cable must be installed in the extended position (no slack)
The Canada Occupational Safety and Health regulations Part XIII, 13:6b states: "Where an air hose is connected to a portable air powered tool used by

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

an employee, a restraining device shall be attached to all hose connections, in order to prevent injury to an employee in the even of an accidental disconnection of a hose."

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

ESPECIFICACIONES TÉCNICAS

Factory Part Number	WB3
Hose ID	1/2" - 2" (13mm - 50mm)
Length	28" (712mm)
Material	Galvanized Carbon Steel
Maximum Operating Pressure	200 PSI
Size	3/16" cable (5mm cable)
Weight Lb	0.4900

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us