DQC WS-BOP SERIES HIGH PRESSURE WINGSTYLE FEMALE PLUG





** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/24/2026 01:01 AM

SKU
: 25658

MARCA
: DIXON VALVE

MODELO
: WS10F10-BOP

Applications:
Designed for use in oil rig BOP systems where couplings are required to operate under fire conditions in an emergency.

Specifications:
BOP Couplings have been fire tested and Lloyd's certified to 700°C (1300°F) in accordance with API 16D. Certificate available upon request.
Lloyd's Test Pressure: 5,000 PSI

Construction:
Machined components are manufactured using solid steel bar stock.
Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Zinc Nickel
Red powder coated external nipple O-ring for easy BOP service identification.
Blow-out Preventer (BOP) couplings contain severe service FKM seals
PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.
Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:
Snap-Tite 75-Series
DNP VFF-HD BOP series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Body Size	1-1/4"
Burst Pressure	25,100 PSI (1700 bar)
Factory Part Number	WS10F10-BOP
Length	5.38"
Material	Steel
Maximum OD	2.63"
Maximum Operating Pressure	5000 PSI (345 bar)
Thread	Female NPTF
Thread Size	1-1/4" - 11-1/2

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us