WAVESEAL CLAMP



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 10:54 PM

SKU
: 21954

MARCA
: DIXON VALVE

MODELO
: WSS44

Applications:
Provides optimal retention in applications involving thermal cycling and / or high vibration.

Features:
Produces a sealing O-ring effect that prevents leakage

Construction:
5/16" head screw
Band: 201/301 Stainless Steel
Liner & Housing: 304 Stainless Steel
Screw: 410 Stainless Steel

Installation
Suggested installation torque 50-70 inch pounds, maximum recommended torque 70 inch pounds

Note:
Clamps sold 10 per box

Safety notes:
Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any assembly installed with this clamp.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Factory Part Number	WSS44
Hose OD From	2-1/2"
Hose OD To	3-1/16"
Material	Stainless Steel
Width	9/16"
Mandatory Pkg/Box Qty	10
Weight Lb	0.1010
Torque	70 in. lbs. Maximum

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us