WILKERSON FRL'S X02 AUTOMATIC DRAIN



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 07:43 PM

SKU
: 26633

MARCA
: DIXON VALVE

MODELO
: X02-04MB

Features:
Metal bowl
5 oz. bowl
Fully automatic, float operated
Full 1/2" NPT drain inlet
Quick-disconnect clamp ring for easy bowl removal when servicing
No electrical connections
Easily installed

How it works:
As liquid contaminants collect in the bowl, they raise a closed-cell cellular float. When the liquid level reaches a given point, the float triggers a mechanism which pilots line pressure against a large area piston or diaphragm which snaps open the drain valve. The contaminants are discharged from the drain orifice at line pressure. As the liquid level falls, the pilot valve closes, line pressure against the piston/diaphragm returns to atmosphere and the drain valve snaps closed.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Description	Metal bowl
Factory Part Number	X02-04MB
Maximum Operating Pressure	200 PSIG (13.8 Bar)
Port	1/2"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.6800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us