POSITIVE DISPLACEMENT FUEL FLOW METER 4"

FECHA
: 11/23/2026 08:45 PM

SKU
: 27824

MARCA
: Meters Control

MODELO
: MC530



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

MetersControl Positive Displacement Flow Meter are designed and engineered in Europe and pass through rigorous tests that ensure accuracy, repeatability and long life. MC offers the ideal solution in a variety of applications, in wich transfer of petroleum products is implicated and high accuracy is required.

TYPICAL APPLICATIONS: Check of loading / unloading operations of fuel and petrochemical products in fuel bulk plants and/or refineries. On truck tanker for fuel transport and delivery. Heavy duty fuel dispensing system for big vehicles and airplanes.

HIGHLIGHTS:
Absolute compatibility with all Veeder Root components
Lack of internal friction (No metal-to-metal contact)
Reduced number of parts
Self-lubricating
Low and easy maintenance
Low drop pressure between parts
Simple and robust design
Bi-directional liquid flow
Meets Worldwide Weights and Measures Standards
Repeatability under diverse conditions and products

Directive 94/9/EC (ATEX) and 2004/22/EC (MID)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Brand	MetersControl
Factory Part Number	MC530
Material	Aluminum, Cast iron
Inlet	4"
Outlet	4"
Flow Rate	35 - 350 GPM (130 - 1300 LPM)
Measure Unit	US Gallons (Liters optional)
Register	Mechanical, Veeder Root VR7887
Accuracy	±0.12% over a range of 5:1
Repeatability	0.05%
Maximum Operating Pressure	150 Psi (10.3 bar)
Viscosity Range	30 to 1,500,000 SSU (1 to 325,000 cps)
Temperature Range	-22°F to 150°F (-30°C to +70°C)
Origin	Europe

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us