IN-LINE LUBRICATOR 1/2"



** Imágenes referenciales*
*** Algunas características pueden variar sin previo aviso, venta sujeta a stock disponible*

FECHA
: 11/23/2026 08:30 PM

SKU
: 27815

MARCA
: TEXAS Pneumatic

MODELO
: TX-0L

Applications:
Designed to protect portable or stationary air tools by efficiently oiling the tool mechanisms.
Each time an air tool is operated, a fine mist of oil is injected into it along with the air from the compressor.

Use:
Type of oil to use: Use any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil.

Features:
Transparent sight disc allows visual inspection of oil level.
Oil flow regulated by screwdriver screw adjustment.
Minimum flow rate is 30 SCFM.

Construction:
Aluminum

Installation
Installation is recommended within 25 feet of the tool to be lubricated.
Refer to the arrow for proper air flow direction.

Safety notes:
Not recommended for constant flow applications. For reciprocating tools only.
Do not use any synthetic oil or oils containing additives or solvents.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

ESPECIFICACIONES TÉCNICAS

Capacity	1.4 fluid oz. oil (40ml)
Factory Part Number	PL300
Female Thread	NPT
Female Thread Size	1/2" (15mm)
Flow	30 SCFM
Material	Aluminum
Maximum Operating Pressure	500 PSI at 70°F (21°C)
Weight Lb	0.8800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us